

Protect Sensitive Digital Equipment with 3-in-1 Anti-static Tarps from THOR

Your sensitive fiber optical switch cost up to \$90,000,000 to install. Are you doing everything you can to protect that switch?


Maybe not, if you haven't implemented THOR's new anti-static protection plan. Our unique anti-static, fire retardant DuraShield™ 8000 ASFR tarps can increase your protection three ways.



Prepare NOW for an upcoming disaster. We have attached a center drain, rope, hose and shut off valve to our anti-static tarp so "The Three-in-One Tarp" will protect your switch if the roof leaks. Simply take the tarp which was being used as a dust partition and suspend it over the digital equipment, saving the day, the fiber optic switch and your customer's satisfaction.



Dust Partition Light construction and carpentry projects raise a lot of dust which can severely damage sensitive equipment. Hang the tarp by its grommets to contain the static charged dust.



- ✓ Virgin polyethylene
- ✓ Rugged woven reinforced construction
- ✓ Strong yet lightweight
- ✓ Available in rolls or custom sizes






THOR DuraShield 8000ASFR Tarps in the Typical Central Office **Switching Facility**

- Dramatically decrease electrostatic discharge in many different areas of the central office
- Save \$1000s in ruined components and lost revenue due to switch downtime
- Take a major step beyond ordinary protection by guarding against both dust and electronic contamination
- White tarp maximizes existing light conditions
- Yellow implies CAUTION and affords privacy of stored tools, equipment
- Green blends in with outdoor earth colors


Protecting Lives, Revenues and Resources





The Rain Drain™ tarp protection kit is like a fire extinguisher on the wall. You hope you will never have to use it, but when you have a leak, you need protection now! Kits come in various sizes, and include a heavy duty hemmed and grommetted tarp, an attached shut off valve, 15' of 34" garden hose and 100' of 400# test polypropylene rope.





THOR Tarps for the Central Office Environment

Specifications

- □ Standard Weight 5.6 oz/yd² or 40#/msf
- **Thickness**
- 12.0 mils
- **Tensile Strength** 185#/inch width

- m Impact Strength 325 psi mullen burst
- Abrasion Resistance > 10,000 flex cycles

Conductive



Anti-static

- Surface Resistivity 10¹² ohms psi
- Static Decay
- < 2 seconds
- **B** Frictional Charging Limit
 - < .13nC psi
- **Bellcore Certified**
- Exceeds Military Spec. #B-8-1705

Certified Ratings



Fire Retardant

- American Nuclear Insurers (ANI)
- National Fire Protection Assoc. (NFPA)
- Scientific Ecology Group (SEG)
- Canvas Producers Assoc. Intl. (CPAI)
- m Mine Safety & Health Admin. (MSHA)
- California State Fire Code
- Boston Fire Marshall's Code

Features

- ☐ Rot and mildew proof, 100% synthetic
- ☐ ANI & NFPA approved as fire retardant
- ☐ Rugged, woven reinforced polyethylene
- ☐ Anti-static, with impregnated conductive grid
- Available in natural, yellow and green
- ☐ Available in rolls or custom sizes, with loops, hems, grommets or Velcro closures





DuraShield 8000ASFR makes a perfect material to create temporary enclosures for protection of static-sensitive equipment during unpacking, moving and storage. Static build-up that could ruin delicate circuits is conducted away from the equipment through the graphite lines which cover the entire tarp surface.

Ordering information and available options

RAIN DRAIN TARP

- Finished sizes: 3.5' x 5' 10.5' x 25' 5.5' x 10' 14.5' x 25' 7.5' x 15'
- Custom sizes on request
- Available as part of the kit or by itself
- Triple-folded, double stitched, nylap reinforced hem; grommets at 3' centers

DURASHIELD 8000ASFR

- Stock rolls from 4' x 100' to 40' x 100'
- Custom sizes up to 30,000 sq. ft.
- Available with Velcro® closures, grommets drawstrings and pipe loops
- · Comes in natural, yellow and green



THOR Enterprises, Inc.

Visit Our Website http://www.thortarp.com THOR Div., ODIN Int'l, Inc. Oconomowoc, WI 53066-0811 Toll Free: 1-888-634-6462