



THOR Tarp

Div. of

ODIN

International, Inc

PO Box 811, Oconomowoc, WI 53066

800-835-8467 TF; 262-569-1511 Fax

<http://www.thortarp.com>



White DuraShield 8000 ASFR Tarpaulin Anti-Static,
Fire Retardant, Waterproof & Chemical Resistant

THOR Part Number: 58451

Verizon Item ID: 360214

4' x 4' White DuraShield 8000 ASFR, grommetted tarpaulin
w/ grommets 2' centers

Specifications

Attribute Tested	Average	Requirement
Weight (oz/yd ²)	11.8	11 +/- 2.0
Cold Crack (-20°)	Pass	Pass
Mullen Burst (lbs)	385	>275
Mullen Hydro (psi)	354	>275
Adhesion (lbs/in)	8.5	>6
Abrasion S1	250	>200
Abrasion S2	75	>50
DuPont Scrub	600	>400
Surface Resistivity @ 10 Volts S1	6.5 x 10 ¹⁰	1 E 12 ohms per sq. max
Surface Resistivity @ 10 Volts S2	6.9 x 10 ¹⁰	1 E 12 ohms per sq. max
Tongue Tear (lbs) (W x F)	62 x 54	>30
Grab Tensile (lbs) (W x F)	217 x 184	>175 x 150
Smoke Resistance	Complies with ASTM E-84 Class 1"A" rating	
Flame Resistance	Complies with NFPA 701, Small Scale	



THOR Tarp

Div. of

ODIN

International, Inc

PO Box 811, Oconomowoc, WI 53066

800-835-8467 TF; 262-569-1511 Fax

<http://www.thortarp.com>



White DuraShield 8000 ASFR Tarpaulin Anti-Static,
Fire Retardant, Waterproof & Chemical Resistant

THOR Part Number: 58452

Verizon Item ID: 360215

8' x 10' White DuraShield 8000 ASFR, grommetted tarpaulin
w/ grommets 2' centers

Specifications

Attribute Tested	Average	Requirement
Weight (oz/yd ²)	11.8	11 +/- 2.0
Cold Crack (-20°)	Pass	Pass
Mullen Burst (lbs)	385	>275
Mullen Hydro (psi)	354	>275
Adhesion (lbs/in)	8.5	>6
Abrasion S1	250	>200
Abrasion S2	75	>50
DuPont Scrub	600	>400
Surface Resistivity @ 10 Volts S1	6.5 x 10 ¹⁰	1 E 12 ohms per sq. max
Surface Resistivity @ 10 Volts S2	6.9 x 10 ¹⁰	1 E 12 ohms per sq. max
Tongue Tear (lbs) (W x F)	62 x 54	>30
Grab Tensile (lbs) (W x F)	217 x 184	>175 x 150
Smoke Resistance	Complies with ASTM E-84 Class 1"A" rating	
Flame Resistance	Complies with NFPA 701, Small Scale	



THOR Tarp

Div. of **ODIN** International, Inc

PO Box 811, Oconomowoc, WI 53066
800-835-8467 TF; 262-569-1511 Fax
<http://www.thortarp.com>



White DuraShield 8000 ASFR Tarpaulin Anti-Static,
Fire Retardant, Waterproof & Chemical Resistant

THOR Part Number: 58453

Verizon Item ID: 360216

10' x 12' White DuraShield 8000 ASFR, grommetted tarpaulin
w/ grommets 2' centers

Specifications

Attribute Tested	Average	Requirement
Weight (oz/yd ²)	11.8	11 +/- 2.0
Cold Crack (-20°)	Pass	Pass
Mullen Burst (lbs)	385	>275
Mullen Hydro (psi)	354	>275
Adhesion (lbs/in)	8.5	>6
Abrasion S1	250	>200
Abrasion S2	75	>50
DuPont Scrub	600	>400
Surface Resistivity @ 10 Volts S1	6.5 x 10 ¹⁰	1 E 12 ohms per sq. max
Surface Resistivity @ 10 Volts S2	6.9 x 10 ¹⁰	1 E 12 ohms per sq. max
Tongue Tear (lbs) (W x F)	62 x 54	>30
Grab Tensile (lbs) (W x F)	217 x 184	>175 x 150
Smoke Resistance	Complies with ASTM E-84 Class 1"A" rating	
Flame Resistance	Complies with NFPA 701, Small Scale	



THOR Tarp

Div. of

ODIN

International, Inc

PO Box 811, Oconomowoc, WI 53066

800-835-8467 TF; 262-569-1511 Fax

<http://www.thortarp.com>



White DuraShield 8000 ASFR Tarpaulin Anti-Static,
Fire Retardant, Waterproof & Chemical Resistant

THOR Part Number: 58454

Verizon Item ID: 360217

12' x 15' White DuraShield 8000 ASFR, grommetted tarpaulin
w/ grommets 2' centers

Specifications

Attribute Tested	Average	Requirement
Weight (oz/yd ²)	11.8	11 +/- 2.0
Cold Crack (-20°)	Pass	Pass
Mullen Burst (lbs)	385	>275
Mullen Hydro (psi)	354	>275
Adhesion (lbs/in)	8.5	>6
Abrasion S1	250	>200
Abrasion S2	75	>50
DuPont Scrub	600	>400
Surface Resistivity @ 10 Volts S1	6.5 x 10 ¹⁰	1 E 12 ohms per sq. max
Surface Resistivity @ 10 Volts S2	6.9 x 10 ¹⁰	1 E 12 ohms per sq. max
Tongue Tear (lbs) (W x F)	62 x 54	>30
Grab Tensile (lbs) (W x F)	217 x 184	>175 x 150
Smoke Resistance	Complies with ASTM E-84 Class 1"A" rating	
Flame Resistance	Complies with NFPA 701, Small Scale	